

Standard Wax / Resin Ribbon

Broad Range Adaptability <<


Excellent Print Quality <<

Lower Print Energy Consumption <<


BRC800 is an economical wax-resin ribbon that provides great print quality and scratch resistance on a wide range of print media- Low energy requirements and Todaytec backcoat technology extend the life of print heads in demanding wax-resin applications.

Appearance


Blackness




Definition



Horizontal Barcode




Vertical Barcode




Resistance

Abrasion Resistance




Scratch Resistance




Other Resistance

Heat Resistance



Corrosion Resistance



Regarding other solvent, fee to consult

Sensitive

Printing Energy



Printing Speed



Applicable

Paper Labels (Coated paper,Hangtag,

etc.)

Synthetic Material (Synthetical paper,

etc.)

Film (PET, etc.)

Washing label



Standard Wax Ribbon

• Parameters of Ribbon

Ink Melting Point: 105°C(221°F)

Carries: PET Film

Carrier's Thickness: 4.5 µ m

Ribbon's Thickness: < 9 μ m

Back Coating: Silicon

Coefficient of Friction: Kc < 0.2

Storage Conditions: 12 months

Temperatures: $5\sim35^{\circ}C(40\sim95^{\circ}F)$

Humidity: 20~80%

• Certificates and Reports

- ISO9001, ISO1401, MSDS, RoHS,
 SGS, SVHC
- No Halogen
- No Toxic Substances of SVHC

• Recommendable fields of Application



Inventory Labels



Logistic



Tickets /Bills



Food Labels



Medicare



Super Market



Tag



ID Card Copy